Certificate of Location of Government Corner

ID#: 732206 **Description:** 1/4 SEC COR 21 22 73 **Date Set:** 6/23/2003 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 6' south of centerline of CSAH 2 and 34 1/2' west of centerline of driveway south
County Survey Disk in PP N 38.60'
This corner is located by GPS measurement

Corner History:

11-1853 Gov't Notes, W.B. Yerby - Set 1/4 section post. Bearing Trees - Burr Oak 7" N48°E 17 links. Burr Oak 8" S32°W 24 links.

4-1858 T. Hunter, Pg. 54, No. 78 - Bearing Trees (N48°E 17 links) (S 32°W 25 links) 1/16 west 19.70 chains M&L to cen sec 21, measure S 39.57 chains to section corner.

5-1875 T. Hunter, Pg. 273, No. 271 found stake remains. Set stone 4x8x18 in its place with stake stub by its side.

6-1876 T. Hunter field Bk. 4, P.140 unrecorded survey. Shows measure west to cent. 19.88' - 19.88', shows measure south 19.911/2 - 19.911/2.

9-1899 R. Fraser, P.644 No.580 found stone. 16S 241/2 links set cedar stake M&L 19.873/4 (1311.9'). 16C SE1/4 21 set stake M&L 19.757/8 (1304.1).

1909 Charles Armstrong, P.120 B found limestone as recorded P.273. 16 S found stake M&L 19.84 (1309.44'). 16C SE1/4 set iron bar as corner M&L 19.771/2 (1305.15).

6-29-1937 County Highway Department Archie A & Art S. B.92, P.10. Found stake in pasture.

5-15-1974 County Surveyor set R.R. spike as corner in line w/fence on line from the east. Will set monument.

10-30-1992 McGhie and Betts found and used R.R. spike 5.5' south of centerline.

8-1996 Dean Strange of Peoples Coop found pk nail in centerline of road.

6-23-2003 County Surveyor found R.R. spike down 0.4' and removed. Set 1" square pipe w/cap at surface.

10-19-2005 County Surveyor found 1" square pipe w/cap at surface in good condition.