Certificate of Location of Government Corner

ID#: 732209 **Description:** SEC CEN 22 73 **Date Set:** 9/2/1965 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls 29' ENE of centerline of CSAH 11 on curve
County Survey Disk in PP #22986 NNW 99.68'
Spike in CP E 32.86'
County highway disk in fence post (new R.R. tie) NE 45.43'
Post w/sign 2' east
This corner is located by GPS reference stations "Leitzen A & B"

Corner History:

5-5-1875 T. Hunter P.273, No.271 found stone boulder avered as corner set by Daniels, tested E-W 1/4 line & proved exact. 16N set stake M&L 19.921/2 N 10'E S 89° 40'East.

1923 County Highway Department Bk.#31 Pg. 26, Found stone.

10-24-1963 J. Kerr set CIM over stone and stake.

9-2-1965 County Highway Department reset CIM after road grading

3-12-1974 County Highway Department (Book 376, Page 14) found CIM and took ties. Used monument for CSAH 2 alignment, PI Station 282+11.0

1989 County Surveyor found C.I.M. in east road ditch.

9-29-1992 Roger Brand & Associates found and used CIM at center of section 22.

10-30-1992 McGhie & Betts found and used CIM.

6-29-1993 Yaggy Colby found and used CIM.

2-17-1999 County Surveyor found CIM in good condition down 0.5'

9-6-2000 Brand & Massey Surveying found and used CIM at center of section 22.

10-18-2005 County survey crew found CIM down 0.5' in good condition. Set post w/sign.