Certificate of Location of Government Corner

ID#: 732304 **Description:** 1/4 SEC COR 23 26 73 **Date Set:** 9/30/1968 **County:** Olmsted

Section: 23 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The monument is down 1.2'
The corner falls 2' south of fence east and 2 1/2' SSW of CP
1" angle iron up 18" N 0.7'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby - 40.00 set temp sec post west on true line between sec. 23&26 8° 58'E. 40.00 set steel post in mound, made trench, & planted osage orange N&S of trench.

5-1867 H.E. Horton, Pg. 84, No.128 Shows 1/4 corner. Measure south 39.50 chains, 1/16 west 19.881/2 chains.

5-1876 T. Hunter P.293, No.288, found stake. Measure west to section corner 39.94. Used 1/4 corner to set center 26.

4-1900 R. Fraser P. 663 No. 590 field book 15 pg. 41-42 Hanhenry. Found post & stake. Drove stake in place of post & set 2 stones, one 2x12x18. 1/16 north set stake M&L. Measure west short 15 links.

9-1968 J. Kerr found stone and old post. Set CIM over stone with 5/8"x12" rod.

10-8-1996 County Surveyor found CIM 8" deep in fence row 2.3' SSW of CP to fence E-W-N & 2' S of fence line east.

8-4-2011 County survey crew found cast iron monument in good condition