Certificate of Location of Government Corner

ID#: 732306 **Description:** 1/4 SEC COR 22 23 73 **Date Set:** 11/4/2005 **County:** Olmsted

Section: 23 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' east of N-S fence and in line with fence west
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby - 40.00 set steel post. Burr Oak 10" N 671/2 W 257 links.
Burr Oak 9" S26 E 310 links.

5-1875 T. Hunter, P.273 No.271 found fence post in mound. Stake been removed in 1874. Corner undesputed. 16N set stake midway 19.95.

4-1900 R. Fraser, P.663, No.590 found post P.273. Drove stake & set 2 boulder stones around it. 16 south drove stake M&L 2632.74 (line short 11 links).

1949 K. McGhie found post used as corner.

9-30-1968 J. Kerr removed stones in wet area set 11/4" x 41/2' galv. pipe as corner with end above ground. 16 south set 1966 M&L 1314.4 iron rod.

9-11-1989 Vince Fangman found and used 1 1/4" pipe in survey for City of Rochester flood control structure (SR-2).

11-4-2005 County Surveyor found 1 1/4" pipe down 0.5' in good condition. Removed 1 1/4" pipe and set 5' telspar pipe w/cast iron cap up 0.1'. Set post w/sign.