Certificate of Location of Government Corner

ID#: 732804 **Description:** 1/4 SEC COR 28 33 73 **Date Set:** 10/17/1972 **County:** Olmsted

Section: 28 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 6' south of centerline of E-W twp road
Bottle cap in E side PP #20221 NW 33.28'
NE corner steel shed SW 69.62'
Old RP nail in E side PP #20234 SSW 29.97'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, Yerby - 40.00 set temp section post west on true line between sections 28&33 8° 52' east. 40.011/2 set section post in mound, made trench, & planted Osage Orange seeds N&S of trench.

4-1857 T. Hunter P.23 No.36. Used corner, set 1/16 north M&L 20.0.

5-1876 T. Hunter, Set stone at 1/16 corner north.

5-1889 T. Fraser P.429, No.417. Set temp pt M&L 40.103/4 (2647.10') 16 east set stone 2"x7"x12". 16N found corner.

11-1892 T. Fraser, P.499 No.470. Found stake set 429. 16 west set stone. 16 east found stone P.429.
16 south set stone. 16 c NW1/4 33 set stone. 16 c NE1/4 33 set stake.

10-17-1972 County Surveyor set CIM over iron in stake hole, Large stone on west side CIM.

8-1979 County Surveyor found CIM in good condition. Used in control survey.

11-1-1989 County Surveyor found CIM in good condition.

10-18-2005 County Surveyor found CIM down 0.9' in good condition.