Certificate of Location of Government Corner

ID#: 732806 **Description:** 1/4 SEC COR 28 29 73 **Date Set:** 11/29/1972 **County:** Olmsted

Section: 28 **Township:** 107N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' east of fence south
40d spike in W side 42" White Oak N 4.63'
40d spike in S side 12" Burr Oak E 43.8'
Post w/sign 1' north
This corner is located by GPS reference stations "Hain B & C"

Corner History:

1853 Gov't. Notes, Yerby - 40.0 set section post. Black Oak 10" N80 E26 links.
Burr Oak 7" N56 W53 links.

5-1858 T. Hunter, P.56 No.81, used corner - Bearing tree N 631/2°W 51 links. 16 south set corner N74° E27 links M&L 19.85 (1310.1). 16W set corner. 16C SE1/4 29 set corner.

5-1859 T. Hunter Pg. 60 No. 86 shows 1/4 post.

1-1872 T. Hunter P.191, No.202 found original corner, 16 south found stake set P.23.
16 east set stake.

5-1876 T. Hunter caption of pg. 23 Bk. A found the original corner from the stumps of the witness trees. Meas N 1312.74 and S 1310.1.

4-1881 T. Hunter, Bk.5, Pg.109 Section 29-32 used corner to set center 29.

1896 T. Hunter Bk. A pg. 602 found the 1/16th stone N. in place.

4-1962 J. Kerr Bk. 83 P.39. Set steel post as corner.

11-29-1972 County Surveyor set CIM over 5/8" rod by measure. Removed J. Kerr steel post.

11-14-1989 County Surveyor found CIM in good condition. Set sign & post 1.0' north.

10-21-2005 County Surveyor found CIM down 0.1' in good condition.