Certificate of Location of Government Corner

ID#: 733204 **Description:** S 1/4 SEC COR 32 73 **Date Set:** **County:** Olmsted

Section: 32 **Township:** 107N **Range:** 13W **Monument Description:**

Reference Ties:

The corner falls 18' north of centerline of CSAH 9 and 16 1/2' east of centerline CR 109 south
County Highway Disk in PP #19110 NW 42.28'
County Highway Disk in PP #47210 SE 78.89'
This corner is located by GPS measurement

Corner History:

Gov't Notes, 40.00 set post for section corner, built mound, made trench, and planted SE Osage Orange & Apple seeds NE.

10-1857 John Fellows (Book A, Page 41, No. 63) shows 1/16 E with measure.

3-1878 T. Hunter, County Surveyor, (Old Field Book 5, Page 43), found stake. Set stone 22"x6"x5" with broken stone around bottom.

6-1899 W. Fraser, County Surveyor, (Book B, Page 658, No. 586) S32, State of MN Found stake, set stone 2"x8"x26". 16W set stake, meas east 40.01 to stone found.

1937 County Highway Department, (Book 88, Page 2), found stone & 1" rod.

1965 County Highway Department set spike with punch mark in corner.

6-1969 J. Kerr, County Surveyor, referenced corner before road construction.

12-1978 R. Brand, County Surveyor; After analizing the data in Field Books # 88 & 186 and checking J. Kerr's field book notes, I came to the conclusion that the current position used as 1/4 is not the Fraser corner as his corner should be about 4' north and 7' west of the current position. There is some confusion between W. Fraser and T. Hunter and the current position could be T. Hunter's stone.

11-23-1983 Vince Fangman took RPs to concrete nail in centerline CSAH No. 9 and 17' east of centerline road south. Set 3/4" pipe at P.K. nail location as final corner. (References gone)

5-30-1989 County Survey Crew found 3/4" pipe 17.8' north of centerline CSAH No. 9 and 16.5' east of centerline of CR. 109 south.

6-23-2003 County Survey Crew found 3/4" pipe and removed. Set 1" square pipe w/cap at surface and measured its position using GPS.

4-24-2017 County Survey Crew found and removed 1" square pipe w/cap prior to road construction.