Certificate of Location of Government Corner

ID#: 733609 **Description:** SEC CEN 36 73 **Date Set:** 10/31/1966 **County:** Olmsted

Section: 36 **Township:** 107N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Cast Iron Monument

Reference Ties:

The corner falls 1' SW of CP to fences N-S-E-W
The monument is down 1'
Sign on CP 1' NE
This corner is located by GPS measurement

Corner History:

9-30-1863 P.C. Compton, County Surveyor, (Book A, Page 77, Survey No. 115), found center section and set 1/16th East M&L.

5-23-1872 T. Hunter, County Surveyor, (Book A, Page 205, Survey No. 213), set stone 2"x6"x12" at true intersecting lines. 1/16th West set stake M&L 19.98 1/2 chains (1319.01') for line south. 1/16th East set stake M&L 19.81 1/2 chains (1307.79') for line north. 1/16th North set stone 2"x4/8"x14" M&L 19.86 chains (1310.76') for line west.

10-31-1966 J. Kerr, County Surveyor, dug and found large stake or small post with small limestone. Set Cast Iron Monument over 1/2"x28" pipe with wood stake on each side with small stone on west side. Corner falls 1.5' west of North-South fence and 7.5' north of corner post of fences south and west, but in perfect line of main fence west. On running East-West quarter line found monument to be 4.45' north of true line.

5-26-1970 County Surveyor, Cast Iron Monument location as center in question and made measurements to prove or disprove. On running East-West quarter line found monument to be 4.3' north of true line.

5-28-1970 County Surveyor dug extensively covering true E-W 1/4 line and found nothing. Accepted Cast Iron Monument as set as corner.

10-20-2006 County Survey Crew found Cast Iron Monument down 1' in good condition and measured its position using GPS. Set sign on wooden corner post facing SW.