Certificate of Location of Government Corner

ID#: 740104 **Description:** 1/4 SEC COR 1 12 74 **Date Set:** 9/15/63 **County:** Olmsted

Section: 01 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in tree line behind house #1310 Buck Ridge Dr NE
24" Burr Oak NNE 6.5'
Post w/sign 2' North
This corner is located by GPS reference stations "Johanns A & B"

Corner History:

Govt. Notes - M. Karrick 1854 40.00 Set temp 1/4 sect. Post West on true line between sections 1 & 12 40.00 Set 1/4 sect. post V8º 41' Burr Oak 9 N 68 W 133 Burr Oak 12 S 20 E 165

5-1857 Thomas Hunter Pg. 24 No. 39 Used 1/4 corner 1/16 No. 19.72 chs. M&L - Bearing Trees (S65 1/2º E 38 lks.) (S 23º W 77 1/2 lks.)

6-1900 Robert Fraser P. 646 to 652 No. 582 corner stake plowed out by farmer plowing too close to hedgerow. Mr. Wm. Schaick was only pioneer who knew of its former location. After relocating corner, this man answered it came exactly as he would have located it. Set new Burr Oak stake between 2 stones. 4" Burr Oak N 3º W 47 1/2 lks. 31.35'. 1/16 North set stake on 70 lks. offset West M&L 19.92 1/2 which came in middle of river. 1/16 East drove stake M&L 19.97. 1/16 West drove stake M&L 19.94 3/8.

9-15-1963 J. Kerr corner stones found and used in recent surveys. Set C.I.M. over iron in wide wooded fence row. Very little if any important fences. Set 3/8" electric fence steel post by corner. Nail in hub in 16" Burr Oak. NNE 6.5'. No east-west fence or property boundaries.

12-18-1997 McGhie & Betts Found C.I.M. in place and took ties to NE Cor. lot 6, Blk. 1 Shady Lane Subd. East 300' and tied to S.W. corner Lot 6, Block 1 277'.

5-28-2003 County Surveyor found CIM down 0.1' in good condition.