Certificate of Location of Government Corner

ID#: 740105 **Description:** SEC COR 1 2 11 12 74 **Date Set:** 8/22/66 **County:** Olmsted

Section: 01 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Steel post on North side and 1" pipe on South side
Nail in hub on 8" Elm NNW 26.2'
Nail in hub on 24" Red Oak N 18.5'
Post w/sign 2' East
This corner is located by GPS reference stations "Giggles A & B"

Corner History:

Gov't. Notes: M. Karrick 1854 80.00 set post for corner to section 1-2-11-12. Errected mound with trench pits. Charred stakes and osage orange seeds of each angle.

1-1900 Robert Fraser P. 646 to 652 No. 582 corner as mound and pits M records, no knowledge or evidence. Ran and measured lines 1/4 1-2 south to S. sec. 11-12 1/3 39.57, 2/3 2612.0. Ran measured lines in east corner 1-2 to west corner 2-11 39.883/4, 2632.6 R.F. Field Bk. 15 P. 4 says12/18/97: 16 West drove stake on M&L 19.943/8 (1316.3) 16 North drove marked stake and stones M&L 19.785/8 (1306.0) RP above 6" brook N25ºE 231/2 lks. (15.5') 1/16 North - 7" Burr Oak N 591/2ºW 36 lks. (15.5') - 12" Red Elm S 21/2ºW 1281/2 lks. (84.8') 16 South drove stake M&L 19.785/6 (1306.0 2 bearing trees) See 1/4 11-12 set stake at distances measured. Mr. Blanchard will set stone. R.F. 1900 B15 P. 14 - Put dry Jack Oak stake and 3 Bearing Trees 4" J.O. N11ºE (31 lks) 2" Burr Oak N26ºW (36 lks.)

8-22-1966 J. Kerr found 2 limstones 4"x8"x12" one above the other at ancient fence corner with 1" pipe on south side set C.I.M. - nail with hub on 8" elm NNW 26.2 - nail with hub on 24" blazed red oak Badly scarred and split in fence line N.18.5

6-16-2003 County Surveyor found CIM at surface in good condition.