# Certificate of Location of Government Corner

**ID#:** 740106 **Description:** 1/4 SEC COR 1 2 74 **Date Set:** 8/21/95 **County:** Olmsted

**Section:** 01 **Township:** 107N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

**Reference Ties:**

The corner falls 49 1/2' West of centerline of CR #133 on curve
County Survey Disk in PP #53495 S 75° E 101.52'
1992 ref. pipe SE 160.53'
Post w/sign 4' West
This corner is located by GPS measurement

**Corner History:**

Gov't Notes - 1854 M. Kerrick 40.00 set temp. 1/4 section post S 13' W on true line between section 1 & 12 39.30 Set 1/4 section post in mound with trench pits, charred stake Osage Orange seeds NE & SW.

5-1857 Thomas Hunter Pg. 24 No. 39 Meas. East 39.82 chains to center section.

6-1883 T.H. Field Book 14 p. 5-6 shows meas. N 20.08 then 19.39 to sec. corner.

6-1900 Robert Fraser P. 646-652 No. 582 found old stake broken off. Mr. Kanelski & son says that it was the right stake. White Burr Oak stake put there by Hunter and these two parties were with him at the time. It jibbed with clearing running east and west. Witnessed trees grubbed and gone. The stake came by side of cattle pass. The stake stood 2 or 3 feet east of brush fence when it was put in place of old stake in pits and mound. New fences 2 or 3 ft. further west of where brush fence stood. Tested corner by measure given by Hunter from corner to 1/16 corner north which were exactly the same, that is the line of fence at 1/16 corner which was set when stake was standing at 80 rods from 1/16 north to twp. line came about where Hunter's said section corner stood at 50 lks. north from fence post. Concluded he was right. Set Burr Oak stake squared and properly marked Took boulder as witness S 26ºE 84 lks. (55.44 red granite). 10" Jack Oak N43ºW 32" (21.12') 16 south set stone and stake marked M&L 19.785/6 (1306.0) Sandstone - Kassler found iron set by McGee as corner. Sandstone run line so. 2615.24. Also ran line from 1-2-11-12 west 1/4 2-11 and set 1/2" iron 373.37 west of 1-2-11-12 then 1977.09 north of 373.37 to 1/2" iron then 35.7' to center line of road. Bearing trees to 1/16 south 1900-W25ºF 6" brook. 231/2 L-15.51, N. 591/2ºW 12" Red Elm 36L (23.76'-1281/3 L 84.7').

1972 McGhie & Betts - Set 5/8" pipe by line & measure over 1/16 stone south.

4-19-1979 County Surveyor found McGhie & Betts pipe and cap in the N-S fence on the east side of C.R. 133 (1979 Remonument Book P. 31, 41)

5-15-1979 County Surveyor 1/16 North: Took shots in the 1/16th fence (east) north of 1/4 corner 1-2 to determine line of fence.

8-7-1979 County Surveyor - Dug for R. Fraser's wood stake assuming that McGhie & Betts set 1/2" pipe set from south (S.E. Cor. 2 over 1/16 corner north) was set correctly did not find stake or any trace of it except dark spot in soil down about 18" and about 18" and about 0.4' NW W of McGhies & Betts pipe. Accepted McGhie & Betts pipe as correct location as it checked within 0.5' of the tie to the boulder S26ºE 84 lks. (55.44') taken by R. Fraser checked bearing with transit compass and found it close (about a 9 foot) boulder is a red granite about 3' diameter and the westerly one of two. Set a C.I.P. cap in 11/2" sq. pipe about 30" long over a RR spike and stones and glass set about 2' deep under N-S fence nearby. Removed McGhie & Betts pipe. Reference points Mn/DOT Copper disc in 6" Elm south - 7.02 and about 59' east of center line crushed rock road.

2-22-1984 County Surveyor found CIM ok.

7-27-1992 County Surveyor took reference for road construction instrument at reference pipe with cap on top of east back slope of CR 133 - 160.53 SE of corner .

8-21-1995 County Survyeor set 1" sq. pipe with cap in rock. Dug into back slope of CR 133 new grade at reference location from before grading.

6-12-2003 County Surveyor found 1" square pipe w/cap down 0.4' in good condition.