Certificate of Location of Government Corner

ID#: 740205 **Description:** SEC COR 2 3 10 11 74 **Date Set:** 8/2/63 **County:** Olmsted

Section: 02 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence
Center 16" Cottonwood W 9.8'
Center 6" Ash N 3.7'
Post w/sign 1' west
This corner is located by GPS reference stations "Chip A & B"

Corner History:

Gov't Notes: M. Kerrick 1854 80.00 set post for corner to section 2-3-10-11. Erected mound with trench, pitts, charred stake & osage orange seeds at each angle.

1-1874 See field book 3 p. 67-70 Hunter P. 237 No. 239 found mound and pits plain with old stake remains in center mound. Set stone 2"x12"x12" running to point at top - 8" Jack Oak N 21 1/4 W. 51 1/2 L. 33.99, 8" Jack Oak S451/2E 21 lks. 13.86. 16W set stake M&L 19.99 (1319.34' with property corner west of above 1/16 5 chains (330'). Then 14.99 1/4 chains (989.5 to S1/4 3 stake with stones found remains stake from bearing tree taken by R. Perry. (See last page for 1900).

6-1900 R. Fraser P. 646 to 652 No. 582 found mound with stone in center avered by John Newelll as true corner, tested by 2 witnesses trees taken when stone set P. 237. 16 N found stones set by Hunter at 13 chains (858' and at 80 rods (1320' getting about 7.1 lks. more - 4.65' this 1/16 stone could have been found by S. Kerr 1916.

6-21-1902 R. Fraser unrecorded field book #10 Pg. 49 surveyed 10 acres in extreme SW corner Section 2. Set stakes at corners from SW Cor. 2 N 10.10 666.6 chain east 9.97 3/16 - 658.19 being same on opposite sides.

1954 J. Kerr B 59 P1 found badly split and eroded limestone undesrupted as true corner, ran line east a rough brushline. 2631.87 with 1413.71 as station where center road and line crosses point corrected. Corner may have been set - detailed line and Pots B. 59. Found 1/2 2-11 easily.

1958 B 73 P. 316 J. Kerr 16W Corner was huge boulder 30" or more with mark on top set 1916 slightly in error or it moved. Rerun section line west 6 1/4 3-10. Moved stone away same set 1/2" pipe up 6" M&L 1314.0 Property line N also set property corners west of 1/16 985.5 456.86W to 1/4 cor. then another 197.66 west for property corner south.

1/16 R.P. 1/16 corner lies 41' north of random boardman fence running east and 3' west of N-S fence at edge of woods. There is an old sickle bar up 3' and old pump spout and various things by side of pipe corner. Cloth on fence wires east of corner. There is a 1/64 iron rod south 651.5 set by McGhie.

8-2-1963 J. Kerr set C.I.M. in place of small limestone.

4-4-1990 County Surveyor found C.I.M. in N-S fence line 24 1/2' west of center line private driveway. J. Kerr cottonwood and ash trees still here. Set sign and post ± 1' west.

1-14-2003 County Surveyor found CIM up 0.3' in good condition.