Certificate of Location of Government Corner

ID#: 740406 **Description:** 1/4 SEC COR 4 5 74 **Date Set:** 11/7/77 **County:** Olmsted

Section: 04 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in a cattle lane in line with fences north and east, 1 1/2' south of fence west and 3' west of east lane fence south
County Survey Disk in N side of PP E 18.16'
County Survey Disk on west side of wood post S 31.66'
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes M. Karrick 40.00 set temp. 1/4 section post south on true line between sections 4&5. 39.52 set 1/4 section post in mound with trench, pitts, charred stakes and Osage Orange seeds NE & SW.

6-1917 J. Kerr P.270B-B-10 P. 19 found stones north and south. Set stone as corner on section line from SE corner 5 north on line 2626 to stone then 1313 to stakes as 1/16 corner then 1281.0 to stone long recorded lately used by D. Williams P.240 B. Divided N1/4 entire section 5 into square 40 S. Measured west 1317.9 4 times setting stakes only. See Center 5 picture plat.

11-17-1977 County Surveyor set a CIM deep over a 1/2"x2' rod on the line from NW4 to SW4 and in line with fence E. corner set so Taylor's Center 4 iron E-W 1/4 line. Corner comes in cattle lane in line with fence N&E, 11/2' south of fence west and 3' west of east lane fence south.

3-5-2002 County Surveyor found CIM in good condition down 0.5'.

4-26-2002 Mn/DOT Survey Crew found monument in good condition.

9-23-2002 Mn/DOT Survey Crew found monument in good condition.