Certificate of Location of Government Corner

ID#: 740509 **Description:** SEC CEN 5 74 **Date Set:** 8/19/2004 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

5/8" pipe w/cap RLS #41814

Reference Ties:

The monument is at the surface
This corner is located by GPS measurement

Corner History:

7-5-1917 John Kerr, Deputy County Surveyor, (Book B, Pages 270-271) set stake midway and on line on east-west quarter line (improper method).

8-19-2004 Massey Land Surveying set 5/8" pipe w/cap RLS #41814 at intersecting quarter lines.

8-31-2007 County Survey Crew found 5/8" pipe w/cap RLS #41814 at the surface in good condition and measured its position using GPS.

9-10-2007 Ed Kuisle, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 5/8" pipe w/cap, as located by GPS in 2007, falls 0.01' south and 0.01' west of the computed center.

1-14-2009 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

1-8-2010 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

2-14-2012 McGhie & Betts, Inc. used computed center at intersecting quarter lines.