Certificate of Location of Government Corner

ID#: 740804 **Description:** 1/4 SEC COR 8 17 74 **Date Set:** 12/14/98 **County:** Olmsted

Section: 08 **Township:** 107N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1' North of centerline of 55th St NW and 25 1/2' East of centerline of 44th Ave NW
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes M. Karrick 40.00 set temp. 1/4 section post west on true line between sections 8 & 17 variable 9º3'. 40.00 set 1/4 section post in mound with trench, pits, charred stake, & Osage Orange seeds NE & SW.

1857 H. Horton P.84 No.129 corner used & set 1/16 W M&L (19.86 1310.76').

7-1857 John Fellows Pg. 26 No. 41. Use 1/4 cor. meas. west 39.78 chs. 1/16 E 19.98 chs. M&L to section corner. 1/16 N 19.98 chs. M&L to center sec.

7-1857 John B. Fellows Pg. 27 No. 43 used 1/4 cor. 1/16 west 19.89 chs. M&L. Prop. line east 24.98 chs. then 14.98 chs. to sec. cor. meas. south 39.54 chs. to cen. sec.

6-1892 T. Fraser P.489 No.464 found stake in center road. Set stone, East-found stake in road as NW Cor. 75 acre plot, East 21.171/2 (1397.55') then 18.681/2 (1233.2').

1935 Co. Hwy. Dept. Book 75, Pg. 36 Found stone set on north side of old stake, 2' below surface of road with 1"x2"x18" stake.

1941 J. Kerr B25 P.37 Found stone with hub on top cascade road survey.

5-1956 J. Kerr B.63 P.12 S line S8 Rossi. Ran south line S8 5259.7. Set 1/16 corner on line 1314.93 from SE cor. 8 or 1/4 distance.

9-1965 J. Kerr - Found stone & hubs 3.5' deep, 1.56' S direct line. Run and remeasure line 2628.0-6 SE cor. 8 1317.35 east to 1/16 pipe.1315.35 from 1/16 to SE cor. 8. Moved CIM to be on direct line. SetCIM over 1/2"x24" rod.

1969 Help McGee city park survey measure south to center 17 as set 2619.2' then 2640.9 to S1/4 17.

11-3-1989 County Surveyor found CIM deep in Twp road, set 10" CIM over CIM.

7-18-1997 County Surveyor found CIM in good condition down 4" in blacktop.

11-12-1997 County Surveyor laid out corner from city. Set PK nail in new blacktop 55th St. 1' N of crack in centerline 55th St. & 51/2' E of B.C. east Curb B 44th Ave. NW.

12-14-1998 County Surveyor set 1" square pipe with cap #15809 as corner in blacktop 55th St NW

7-26-2001 Mn/DOT Survey Crew found monument in good condition.

3-13-2002 County Surveyor found 1" square pipe w/cap at surface in good condition.