Certificate of Location of Government Corner

ID#: 741204 **Description:** 1/4 SEC COR 12 13 74 **Date Set:** 4/24/78 **County:** Olmsted

Section: 12 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 300' east of centerline of TH 63
SW corner of house NNE slope measure 112.0'
SW corner of house NW slope measure 95.75'
SE corner of house NW slope measure 86.85'
Post w/sign 2' South
This corner is located by GPS reference stations "Archery HQ A & B"

Corner History:

6-1854 Gov't Notes M.G. Karrick, Deputy Surveyor West on true line between sections 12 and 13. 40.00 chs. Set quarter section post. White Oak 10 in. S30ºE 300 lks. White Oak 12 in. N25ºE 400 lks.

10-1859 Thomas Hunter, County Surveyor, (Book A P. 63 No. 89) used this corner to set the 1/16th North and the Center 12.

2-1878 Thomas Hunter (Book A P. 330 No. 324) found the old stake standing in the fence.

1-1900 Robert Fraser, Deputy County Surveyor, (Book A P. 648 No. 582) found a 3" thick stone sticking up in the N-S fence line avered by a Mr. Makon to be the correct corner. Used the corner to set the Center 12.

3-1902 William Fraser, County Surveyor, (Book B P. 32) found the corner of Survey No. 582. Used this corner to set the 1/16th North.

4-1931 John Kerr, County Surveyor, (Kerr Book 5 P. 45-46) found the stone. Drove a large stake by its side.

4-1948 John Kerr (Kerr Book 37 P. 50) found the stone. Used the corner to set the 1/16th West.

1963 John Kerr (card and cert.) removed the stone and set a C.I.M. over a 5/8"x14" iron as the corner.

1978 Mn/Dot found Kerr's C.I.M. pulled out.

4-24-1978 County Surveyor dug and found the 5/8" rod (down 18"). Set a C.I.M. over the 5/8" rod.

12-16-1997 McGhie & Betts Found C.I.M. 300 feet east of centerline T.H. 63 and checked the references.

6-16-2003 County Surveyor found CIM down 0.1' in good condition.