Certificate of Location of Government Corner

ID#: 741205 **Description:** SEC COR 11 12 13 14 74 **Date Set:** 12/4/86 **County:** Olmsted

Section: 12 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and in centerline of twp road south
Minnesota Highway Disk in NW side PP #34397 SW 54.58'
Minnesota Highway Disk in NE side PP #34398 NW 48.13'
Spike in NE side PP #34398 NW 48.07'
Spike in SE side PP #34397 SW 54.43'
This corner is located by GPS measurement

Corner History:

Gov't Notes - June 1853 M. Karrick 80 chs. set post for corner B.T.'s Burr Oak 12 S36ºW 185 Burr Oak 7 N83ºW 165 Burr Oak 9 N26ºE 36 Burr Oak 9 S49ºE 97

2-1878 T. Hunter Page 329 No. 323 found stake with stones on 2 sides in center of road. Tested SE & NW Bearing trees and stumps of LW BT. Set 3"x9"x20" stone with other stone below. 16 west set stake M&L 19.98 meas. east 39.96. Page 330 No. 324 S13. O Brook and others found stone set above. Page 329 also 1/16 corner east.

6-1900 Robert Fraser P. 646 to 652 No. 582 found boulder stone with a pointed stone below. Bearing trees gone. Measure north 1 1/2 miles short 127 lks. (R. Fraser field book 15, Pg. 3-20).

4-1948 John Kerr B 37, P. 50 Ran line N1/4 13 West (Set 1" pipe at 1842.2 118.7 to SE cor. house) from west total 2627.85.

10-1948 John Kerr B 39, P. 67. Found stone set 1/16 W 1313.92 east found 1/4 13-14 south .2636 with property corner 1812.25 south.

9-9-1963 John Kerr - Corner found and used many years Set C.I.M. over 1"x19" rod junk & stones Spud power pole NW 48.0 Spud power pole SW 54.5 Spud 18" burr oak NNE 28.0 Fence lines running north lines with corner.

12-4-1986 County Surveyor Dug down and found C.I.M. and placed another on top and took references.

12-18-1997 McGhie & Betts Found C.I.M. in centerline of tee intersection and found 2 references.

5-28-2003 County Surveyor found CIM down 0.3' in good condition.