Certificate of Location of Government Corner

ID#: 741206 **Description:** 1/4 SEC COR 11 12 74 **Date Set:** 8/6/75 **County:** Olmsted

Section: 12 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls North of Zumbro River
Spike & County Survey Disk W side 8" Elm S37°W 7.60'
Spike & County Survey Disk NW side blazed 8" Elm N64°E 24.55'
spike and County Survey Disk NE side 9" Box Elder N25°W 38.0'
Bottle cap on S side 18" Box Elder N85°W 53.1'
Post w/sign 1 1/2' south
This corner is located by GPS reference stations "HOH A & B"

Corner History:

6-1854 Gov't Notes Michael Karrick, Deputy Surveyor North between sections 11 and 12. 40.00 chs. Set quarter section post. Cottonwood 14 in. S18W 75 lks. Cottonwood 12 in. S83E 190 lks.

6-1900 Robert Fraser (P. 646 to 652 No. 582), County Surveyor, states corner and bearing trees washed out by river. Drove Bur Oak stake and put stones around it as corner midway and on line. A Mr. Van Schart avers midway and on line location very near where presumed corner to be.

8-1975 County Surveyor dug and probed extensively at midway and on line location but found nothing. Set 16" C.I.M. over 3/4"x18" rod midway and on line by electronic traverse computation. Set steel post along side of monument. 1/16 N set 3/4"x30" rod. Rps-spike on east
side 30" white oak SW 35.9, spike in east side 18" white oak SE 18.1, spike in south side 4" elm W 8.0.

4-4-1990 County Surveyor found the cast iron monument and 1975 references in place. Set survey marker sign and post 1 1/2' south of corner.

12-16-1997 McGhie and Betts found CIM in place and checked the ties.

11-20-2003 County Surveyor found CIM in good condition down 0.8'.