Certificate of Location of Government Corner

ID#: 741409 **Description:** SEC CEN 14 74 **Date Set:** 4/18/1900 **County:** Olmsted

Section: 14 **Township:** 107N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Limestone

Reference Ties:

Post w/sign 1 1/2' west
This corner is located by GPS reference stations "Sand & Gravel D & E"

Corner History:

2-4-1878 Pg.329 No.323; Run true inters. Lines with transit set stake & took bearing tree, S65°E 5" Jack oak 7 1/2 links. 16 west set stake, 16 north set stone, RP- 4" burr oak N84°W 24 links, 16 south set stake, 16 center set stake.

3-13-1889 T.Fraser Pg.437 No.424; Found old stake remains and part of witness tree. Renew stake.

4-18-1900 R. Fraser Pg.665 No.591; Unreadable caption explaining stone & stake as center by W.Fraser who found stake and set stone at center.

6-1952 J. Kerr found stone, at center drove 1"x4' rod beside stone at Center 14.

4-22-1954 John Kerr found and used limestone with 1" rod on east side.

12-28-1959 John Kerr found and used limestone with 1" rod on east side.

3-26-1972 County Surveyor found 4" ž limestone with 1" rod on east side up 10" centering over stone.

3-26-1973 County Surveyor found small iron rod with 1/2" pipe forced into rod on top about 2' at 1/16th corner set in 1952. Set M&L 1316.33 to stone at Center 14 & pipe in place as 1/4 14-23.

3-28-1973 County Surveyor found J. Kerr rod at 1315.84 S. of center 14 and 1.35 west. M&L 1319.76. Set 1/2" rod on final line on dike top, 1277.24 N to Center 14 1362.28 S. to final.

6-3-1982 McGhie & Betts found and used stone.

5-9-1989 County Surveyor found 1" iron & stone, iron flush with surface in woods, set post & sign 1.5 west.

12-17-2003 County Surveyor found 1" iron at surface in good condition.

9-13-2007 County Surveyor found stone and witness iron in good condition. Removed witness iron and set 4-1/2" iron rods on each side of limestone as witness.