Certificate of Location of Government Corner

ID#: 741704 **Description:** 1/4 SEC COR 17 20 74 **Date Set:** 3/7/02 **County:** Olmsted

Section: 17 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 27' East of fence South
Post w/sign 1 1/2' North
This corner is located by GPS measurement

Corner History:

Gov't Notes. June 1854 Michael Karrick Deputy Surveyor 40.00 Set temp 1/4 sect. post West on true line between sects. 17 & 20 V9°24'. 40.00 set 1/4 sect. post in mound with trench, pitts, charred stake, & Osage orange seeds NE & sw.

7-1857 John B. Fellows Pg. 27 No. 43 used 1/4 cor. meas. north 40.36 to cen. sec. 1/16 west 20 chs. M&L, 1/16 East 19.69 chs. M&L.

7-1857 T. Hunter Pg. 36 No. 57 shows 1/4 post. 1/16 west 19.80 chs. M&L to sc. cor. - 1/16 East 19.69 chs. M&L to sec. cor.

June, 1863 P.C. Compton, Pg. 75 No. 109 used 1/4 cor. to set center 20 and subdivide N.E. 1/4 sec. 20.

6-1892 T. Fraser P. 489 No. 464, found SW 17 and 1/16 corner east at 19.97 on direct line east at 19.981/2, found stake or post under old fence - set stake as corner.

5-1969 J. Kerr Set CIM above old fence post broken off, spade and glass under E-W fence.

1973 Mcghie & Betts, East 2590.68 - West 2636.80.

2-23-1984 County Surveyor set sign and post 11/2' south of CIM.

3-4-2002 County Surveyor found CIM down 0.2' leaning Northerly.

3-7-2002 County Surveyor removed CIM and found old steel fence post down 2.1' in good condtion. Removed old steel fence post and set 6' telspar w/CI cap at surface at steel post location.