Certificate of Location of Government Corner

ID#: 741705 **Description:** SEC COR 17 18 19 20 74 **Date Set:** 4/29/2010 **County:** Olmsted

Section: 17 **Township:** 107N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #42638

Reference Ties:

The corner falls in centerline of inside lane of round about
The monument is at surface
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes M. Karrick, 80.00 set post for corner to sect. 17-18-19-20. Erected mound with trench, pitts, charred stake, & Osage Orange seeds at each angle.

7-1857 John B. Fellows, Pg. 27 No. 43 Used Sec. corner 1/16 East 20 chs. M&L to 1/4 corner.

7-1857 T. Hunter Pg. 36 No. 57 Shows Sec. corner 1/16 East 19.80 chs. M&L to 1/4 post.

10-1877 T. Hunter P. 321 No. 315 Found nothing.

6-1892 T. Fraser, Found stone claimed by J.W. Right. 16 Ea. found 2 stakes close together on direct line to past found as S1/4 17. 11/2 lks. longer on each side east 19.97.

1936 CHD Found pointed boulder in center of twp. Road.

5-9-1969 J.Kerr set CIM by line of 1/16 & 1/4 corner East 14-20-18.0 1.0; Disc in corner post 10' north of west 38.6 Center 36" Burr Oak near farm house NNW 208.0. Center metal tele. Terminal box NNW 135.3.

2-14-1984 County Surveyor found CIM 2' deep in center of N-S road. Road to soft to set new CIM but set 3/4" rerod at road surface for temp corner.

3-5-2002 County Survey Crew found 3/4" rerod down 0.3' in good condition.

3-20-2002 County Survey Crew removed rod and found CIM down 2.1'. Set CIM over existing location down 0.2'.

7-9-2008 County Survey Crew found CIM down 0.2' w/head broken off.

7-14-2008 County Survey Crew removed CIM for construction.

4-29-2010 County Survey Crew set 1" square pipe w/cap at surface from GPS coordinates.