Certificate of Location of Government Corner

ID#: 741804 **Description:** 1/4 SEC COR 18 19 74 **Date Set:** 10/7/86 **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 11 1/2' south of CP to fences N-S-E
Post w/sign 1/2' east
This corner is located by GPS reference stations "Till A & B"

Corner History:

1854 Gov't Notes: M. Karrick; 40.0 set temp 1/4 section post N89° 53'E on true line between setions 18 & 19.

10-1877 T. Hunter Pg.321 No.315; Corner post of fences avered by Fred Postier and D. Nooman as in exact spot orig. stake in mound stood . Meas. West 38.25 to corner stone set, 16 south set burr oak stake M & L 19.98.

7-1890 Thomas Fraser Pg.445 No.430; Found post Pg.321 with marked wood piece tacked to post. Accepted post as corner (set 10x10x24. Note in field book Pg.66 6" burr oak S25W 6 links. 16 south set stone, and 16 north set stone

1957 McGhie meas. from west to corner post 2524.5 which is recorded distance.

6-4-1974 County Surveyor - Found 8" sq. top limestone about 11/2' So. of field post top of stone down ± 1' - McGhie & Betts had PK nail in top of post leaning east. Bearing tree (± 14" oak, south 4.5' T. center of tree).

10-7-1986 County Surveyor found limestone 10"x10" at middle by 20" long, down 1' and standing 11/2' S. of current corner post to fence N-S-E and 2.3 W and 1.0 south of old post. Dug on west side and pushed stone west to make room for CIM. Set CIM over 1/2" rerod up to ground level. Set survey marker sign and post .4 east.

3-21-2002 County Surveyor found CIM at surface in good condition.