# Certificate of Location of Government Corner

**ID#:** 741906 **Description:** W 1/4 SEC COR 19 74 **Date Set:** 10/3/1963 **County:** Olmsted

**Section:** 19 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

**Reference Ties:**

The corner falls 41' NE of centerline of twp road on curve
County highway disk in SW side PP #92255 NW 53.35'
SE corner garage foundation NE 78.7'
Post w/sign 1/2' North
This corner is located by GPS measurement

**Corner History:**

1853 Gov't Notes: Karrick; 40.00 set post and drove charred stake, built mound, dug trench, and plantedSE osage Orange seeds and NE apples seeds for quarter section corner.

10-1877 T. Hunter Pg.321 No.315
Found stake remains of old stake driven center crossroads by C. Postier and J. Waldron when original stake stood.
1/16 north set quarred stone 3x5x18 M & L 19.95.

7-1890 Thomas Fraser Pg.445 No.430 South 18-19; Found stone set by Postier where corner stake stood.

10-1936 county highway department Bk #89 Pg.76; 1/16 north found limestone monument abput 1 1/2' below surface in center of road. Placed 2x2
Hub on top measure west 1/4 19 to 1/16 corner 1315.5.

8-1940 county highway department found stone monu. And placed 1" iron pin 24" long on north side of stone. RPs- disc in 24" elm SW 45.0', disc in tele. Pole NW 44.0'.

10-3-1963 J.Kerr set CIM over pipe.

9-1966 J.Kerr Bk.94 Pg.54; 1/16 iron north found .29' east of line angle. 1/16 center 19 north 2510.3 east of above 1/16 corner stone as recorded found 5-1967 Bk.92 Pg.13. Set pipe corners east from 1/16 corner 1170' then 495' then 845.3 to 1/16 stone.

1968 Co. H.D. - found CIM.

6-4-1974 County Surveyor retied monument set by Co. H.D. crews and measured E.

2-20-2002 County Surveyor found CIM up 0.1' in good condition.

8-20-2002 County Surveyor set post w/sign 1/2' North.

1-31-2005 1/16th N: County Surveyor found 1/2" rerod down 0.5' in good condition.

5-18-2007 County Surveyor found CIM up 0.1' in good condition.