Certificate of Location of Government Corner

ID#: 742204 **Description:** 1/4 SEC COR 22 27 74 **Date Set:** 11/4/98 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 14W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline 18th Ave NW and in line with chain link fence west between house #2605 and #1801
County Survey Disk in PP #18078 ENE 24.84'
North edge storm sewer MH S 29.45'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes, M. Karrick, 40.00 set temp. 1/4 sect. post west on true line between sects. 22-27. 40.00 set 1/4 sect. post in mound 8deg. 54' with trench, pitts, charred stake and Osage Orange seeds NE & SW.

5-1857 T. Hunter Pg. 24 No. 38 used 1/14 cor. meas. south 40.35 chs.

1936 County Highway Department Bk.81, Pg. 56 - Set hub for corner midway and between NW 27 & NE 27, Dist. 2655.8 in both halves.

1941 J. Kerr - Ran line SE 22 to SW 22. Set point midway (2655.16) 1" pipe placed 11.96' north of true line.

12-21-1954 McGhie shows 1" pipe 6' below surface.

3-23-1956 McGhie set Judical monument (brass plate in concrete) at corner.

11-1969 Note by J. Kerr: Not known as to fate of corner.

11-4-1998 County Surveyor set 1" square pipe w/cap #15809 from MN/Dot traverse station and lot and block information in area.

6-12-2002 Mn/DOT Survey Crew found monument in good condition.

8-27-2002 County Surveyor found 1" square pipe with cap at surface in good condition.