Certificate of Location of Government Corner

ID#: 742205 **Description:** SEC COR 21 22 27 28 74 **Date Set:** 7/20/64 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Locate corner by going to inter 25th Ave NW & 26th St NW, then go north between house #2503 & #2461 to back of lot
County Survey Disk in NW side PP SW 1.29'
Center of 4' tall concrete IBM Marker E 6.15±
This corner is located by GPS reference stations "Haydon A & B"

Corner History:

1854 Gov't Notes, M. Karrick, 80.00 set post for corner to sect. 21-22-27-28 in charred stake, trench, pitts, & Osage Orange seeds of each angle.

1870 R. Perry P. 178 No. 189 - Reviewed and used corner.

1936 County Highway Department Bk. 81 Pg. 56 - Stone in fence corner.

1941 J. Kerr - Used corner a limestone now. Meas. north 5335.4 set no 1/4 corner north.

7-20-1964 J. Kerr set CIM to preserve corner. Corner lies within 1.0' large trans. pp. Northwest corner northgate 3 subd.

10-21-1986 County Surveyor found CIM down .7' on NE side pp, .75' NE of NE side of pole.

5-10-2002 Mn/DOT Survey Crew found monument in good condition.

8-1-2002 County Surveyor found CIM down 0.6' in good condition.