Certificate of Location of Government Corner

ID#: 742206 **Description:** 1/4 SEC COR 21 22 74 **Date Set:** **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 14W **Monument Description:** Corner falls in detention pond

Reference Ties:

This corner is located by GPS reference stations "IBM Park A & B"

Corner History:

6-1854 Gov't Notes, Michael Karrick, Deputy Surveyor, North between sections 21 and 22. 40.00 chs. Set quarter section post in mound with trench, pits, charred stake and planted Osage orange seeds N.E. and S.W.

1863 P.C. Compton (P. 74 No. 107), County Surveyor, used corner to set Center Sec. 21.

1941 John Kerr (B. 24), County Surveyor, used corner to set Center Sec. 22.

J. Kerr indicates 1/4 Cor. M&L, measurement of 2680 to south.

1955 McGhie has notes to indicate they talked to Kerr who told them he set center 22 and a mark on W1/4 line sec. 22 on E. side of TH #52. McGhie projected line west and intersected N-S sec. line of NW 22 to SW 22. This was 1/4 location used in the IBM boundary survey by McGhie Either McGhie or Sandstone set a cast iron monu. at or near
the corner used in IBM survey.

2-1956 Ken McGhie, a surveyor, reset corner for IBM complex at the intersection of the E-W 1/4 line of Sec. 22 and the N-S section line of N.W. Sec. Cor. 22 to S.W. Sec. Cor. 22.

8-7-1975 County Surveyor extended line by elec. trav. from E1/4 cor. sec 22 (a broken top CIM) over the center Sec. 22 (notches cut in MH ring at intersected point) and intersected N-S Sec. line. Removed former CIM and rod under it and set CIM at our location which moved .28' so. and 1.98' east.

6-26-1990 County Surveyor found CIM at IBM in good condition. Post and sign ± 1' west.

8-1-2002 County Surveyor visited area of corner. Corner destroyed by detention pond construction.