Certificate of Location of Government Corner

ID#: 742209 **Description:** SEC CEN 22 74 **Date Set:** 8/15/2007 **County:** Olmsted

Section: 22 **Township:** 107N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Chisel marks on manhole ring

Reference Ties:

Top center hydrant NW 45.68'
PK nail in NW side PP #17413 SW 53.69'
This corner is located by GPS reference stations "Adams A & B"

Corner History:

5-14-1870 Perry P. 178, No. 189 NE 1/4 22 Set stake inters. lines - east 40.09 N 40.19.

1941 J. Kerr, B. 24, P. 77 Set corner later destroyed.

6-1947 J. Kerr B. 34 P. 58 Corner torn out by sewer line.

3-16-1957 K. McGhie set monument at center of section.

8-9-1963 J. Kerr - Chisel marks in manhole ring; Top center hydrant NW 45.43. Sp power pole SW 43.63. 5/8" iron block corner pin NW 50.57. Use notches cut in manhole ring and intersect them to locate point for corner.

3-28-1974 McGhie & Betts found and used chiseled marks on manhole ring.

10-26-1976 McGhie & Betts found and used chiseled marks on manhole ring.

11-17-1977 Yaggy Associates found and used chiseled marks on manhole ring.

7-16-1986 Yaggy Associates found and used chiseled marks on manhole ring.

6-9-1992 Yaggy Colby found and used chiseled marks on manhole ring.

5-10-2002 Mn/DOT Survey Crew found chisel marks on manhole ring in good condition.

8-27-2002 County Surveyor did not find chisel marks on manhole ring. A new manhole was set in 1998 reconstruction of 18th Ave NW.

8-15-2007 County Surveyor set chisel marks on manhole ring from computed coordinates. Did not find property pin NW, top center hydrant NW 45.68' and PK nail in NW side of PP #17413 SW 53.69'