Certificate of Location of Government Corner

ID#: 742404 **Description:** 1/4 SEC COR 24 25 74 **Date Set:** 8/17/63 **County:** Olmsted

Section: 24 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Center blazed White Oak E 118.4'
Spike in NW side blazed 8" Elm NNE 13.75'
Post w/sign 2' South
This corner is located by GPS reference stations "Glendale A & B"

Corner History:

1854 Gov't Notes, M. Karrick, 40.00 set temp. 1/4 sect. post west on true line between sects. 40.00 set 1/4 sect. post in mound 24 & 25 with trench, pitts, charred stake V 8°32' and Osage Orange seeds NE & SW.

Sept. 1858 T. Hunter Pg. 56, No. 82 shows 1/4 post used for breakdown in N1/2 Sec. 25.

8-1876 Hunter, P.303, No.298 Found stake set P.300 and 1/16 west.

12-1900 W. Fraser, P.700, No.616 Used stake just wet of cor. post. 16 east set stone and stake by doubling line from 1/16 corner east of center 25 over 1/16 north 19.931/2, which also proved line & midway N1/4 25 and NE 25 which was 19.78 (1305.48').

12-1-1961 J. Kerr - Ran and meas. line east to limestone at 1/4 24-25, set 11/4" pipe as 1/16 for line north M&L 1332.85 or 2665.70 for the 1/2 mile, ran line north from 1/16 pipe to 1/16 on N. side of SW 1/4 24. A corner set M&L 1331.22 or 2662.44 for 1/2 mile. Set property corners at 1/16 1307.8 M&L, then at 1634.75 both for lines east then at 1961.7 for line west 653.9 from N.

1962 J.Kerr B.71, P.11 Corner then 4x12x12 limestone west 2665.7. South 1319.41 M&L to iron set . 30.3 NE center 15" woak also shows N-S1/16 line east of center woak stone set midway 1315.7

8-1962 J.Kerr shows CIM at 1/4 24-25. shows limestone found east at 1303.5 - set 1/2" rod by stone. Shows 5/8"x6' rod set in boggy land as section corner at 2607.0. Shows stone found so. of above 1/16 on N-S1/16 line at 1314.92 with 1/2" rod just SW of stone.

8-17-1963 J.Kerr set CIM, corner lies 2' east of fence S. under E-W fence. Center blazed woak in fence E 118.4 - center blazed WO SSW 30.7, nail 8" Elm or Boxelder NNE 13.6.

2-16-1976 County Surveyor found CIM approx in line with E-W fence and 3' E. of N-S fence, now all wire on the ground and corner post knocked over.

2-17-1976 County Surveyor found Kerr's iron beside a stone at the 1/16 East. Corner approx. 30' West of fence south and in line of E-W fence.

11-26-1984 County Surveyor 1/16 East of 1/4 Cor. 24-25: Found 31/2" thick pointed limestone flush with ground. Drove concrete nail in top of stone for shot. There is a 1/2" re-rod at the SW Cor. of stone .10 so. & .15 W. of nail. There is a T-bar with disc #10942 .475 and .22 west of the nail.

12-11-2003 County Surveyor found CIM up 0.2' in good condition. White Oak SSW is gone.