Certificate of Location of Government Corner

ID#: 742504 **Description:** 1/4 SEC COR 25 36 74 **Date Set:** 4/12/78 **County:** Olmsted

Section: 25 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

Corner falls in centerline of 11th Ave NE and 14th St NE
SE Cor. House Fdtn. NW 93.08'
County Survey Disk in PP NE 38.30'
Top center water hydrant SW 43.65'
NE Corner house Fdtn. SW 75.17'
County Survey Disk in Able Cable pole SE 42.71'
This corner is located by GPS measurement

Corner History:

6-1854 Gov't Notes M.G. Karrick, Deputy Surveyor, West on true line between sections 25 and 36. 40.00 chs. Set a quarter section post in mound with trench and pits and charred stake. Planted Osage Orange seeds N.E. and S.W., 80.00 chs. To section corner.

5-1856 T. Hunter Pg.8No.13 shows 1/4 post 1/16 north 19.73 chs. M & L to center section

7-1859 T. Hunter Pg.62 No.88; 1/16 north 19.73 chs M & L to center sec.25, 1/16 east 19.97 chs M & L to section corner. Rps to 1/16 East (N59°E 71 links 19" burr oak)(S 81 1/2°E 92 links 10" burr oak)

2-1942 The County Highway Department (C.H.D. Book 107 P. 1) records a stone monument under a 3/8" iron rod.

8-1962 John Kerr found limeston monument. Set CIM at this location.

4-12-1978 The County Surveyor dug and found a 6"x8"x24" ± limestone. Broke off the top portion of the stone, set R.R. Spikes on the East and West sides of the stone, and set a 12" C.I.M. over all.

10-10-2003 County Surveyor found CIM at surface. Top has been worn but still able to see center marking.