Certificate of Location of Government Corner

ID#: 743204 **Description:** S 1/4 SEC COR 32 74 **Date Set:** 10/19/1963 **County:** Olmsted

Section: 32 **Township:** 107N **Range:** 14W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 14' north of centerline of E-W bike path
Spike in 16" Pine NE 42.63'
County highway disk in PP E 27.95'
Spike in 16" Pine NNW 26.18'
Post w/sign 1' north
This corner is located by GPS reference stations "McDivot's & Hole #9"

Corner History:

Gov't Notes - 40.00 sect. post for 1/4 section corner. Burr Oak 10D3 W83, Burr Oak 14 D 3 W207.

Nov. 1856 T. Hunter Pg. 19 No. 31 shows 1/4 Post 1/16 west 19.71 chs. M&L. Meas. north 39.30 chs. Meas. south 39.50 chs.

10-1894 W. Fraser P. 554 No. 511 Fritsch, Engle. All traces & evidence of corner gone, relocated corner M&L 39.771/2. Set stone with stake by its side. 16 east set stone & stake M&L 19.883/4.

10-1963 J.Kerr found rod in place set by McGhie. Set C.I.M. over rod to hold corner as placed. Center 15" Spruce NNW 25.6 Center 15" spruce NNE 27.75 center wrinkled bark tree in drive entry W 74.8.

1-17-1974 County Surveyor, Found C.I.M. down 8"

3-1979 County Surveyor set sign and post 1' north of monument.

8-23-89 County Surveyor found C.I.M. in good condition with sign & post in place.

2-4-2002 County Surveyor found CIM down 0.8' in good condition.

6-19-2006 County Surveyor found CIM down 1' in good condition.

2-5-2008 County Surveyor found CIM down 1' in good condition.