Certificate of Location of Government Corner

ID#: 743405 **Description:** S SEC COR 33 34 74 **Date Set:** 12/4/2013 **County:** Olmsted

Section: 34 **Township:** 107N **Range:** 14W **Monument Description:** 1" Brass Plug with Punchmark

Reference Ties:

The monument is at the surface
The corner falls 40' south of center median of 2nd Street SW
2.8' south of center of sanitary sewer MH
Center top nut fire hydrant E 61.02'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes, Ball, Deputy Surveyor, West between sections 3 and 34. 80.00 chs. Set post for corner to sections 3,4,33, and 34. Dug trench per instructions. Burr Oak 18 in. N72E 453 lks., Burr Oak 16 in. So. 270 lks.

10-6-1892 Thomas Fraser, (P. 495 No. 468), Co. Surveyor, states corner gone. Reset stone from stone set by Hunter 2 rods north and remains of bearing trees.

12-29-1919 C. Armstrong, Book B, Page 298, found and used stone

1-4-1936 John Kerr (B. 10, P. 70), County Surveyor, states 3/4" pipe over stone.

8-25-1941 J. Kerr shows 3/4" pipe and bolt over stone monument.

6-17-1964 John Kerr set C.I.M. over stone. Took ties

6-9-1970 County Surveyor referenced corner for road work.

7-18-1975 County Surveyor, corner cut out in street work. Reset C.I.M. over 1/2"x18" rod from reference points provided by City of Rochester Engineer.

1-8-1997 MN/DOT survey crew found CIM in good condition. They checked ties and added hydrant ESE of corner.

3-5-2002 MN/DOT survey crew found CIM in good condition.

8-1-2002 County survey crew found CIM at surface in good condition.

9-12-2003 County survey crew found CIM at surface in good condition. Set 2 pts and tied out corner for street construction. Removed CIM and 1/2" rod.

12-3-2004 County survey crew set 1" square pipe w/cap at surface from 2003 street construction tie out.

8-14-2007 County survey crew found 1" square pipe w/cap at surface in good condition.

9-19-2013 County survey crew removed 1" square pipe with cap for road construction project.

12-4-2013 County survey crew set 1" brass plug with punchmark at previously measured GPS position.