Certificate of Location of Government Corner

ID#: 743406 **Description:** 1/4 SEC COR 33 34 74 **Date Set:** **County:** Olmsted

Section: 34 **Township:** 107N **Range:** 14W **Monument Description:**

Reference Ties:

This corner is located by GPS reference stations "Alaska A & C"

Corner History:

1854 Gov't Notes, Karrick, Deputy Surveyor, North between sections 33 and 34. 40.00 chs. Set quarter section post in mound with trench and pits and charred stake. Planted Osage Orange seeds N.E. and S.W.

1941 John Kerr (P. 68 B. 25), Co. Surveyor, used the fence corner as corner.

3-1959 McGhie, a Surveyor, had 1" pipe as corner on north creek bank in fence line placed by line from 1/4 Cor. 34-35 over Center 34.

6-19-1975 County Surveyor, corner now comes in large drainage ditch. Found 11/4"x40" shaft badly bent. Staightened shaft and reset at same E-W location as found and on E-W 1/4 line of Section 34. Set a cast iron witness corner over 1/2"x12" rod 111.81' North on section line.

10-1986 County Surveyor, witness corner still in place. Sign gone.

10-7-2002 County Surveyor found Mn/DOT witness corner in good condition. Set 2 points to GPS.

9-11-2003 Witness Corner: County Surveyor found CIM down 0.9' with head broken off in good condition.

Mn/DOT Witness Corner: County Surveyor found 5/8" pipe up 0.3' in good condition. Post w/sign 2' South.

9-13-2007 Witness Corner: County Surveyor found CIM w/head broken down 0.1', removed. Found 5/8" rod down 1.3' in good condition. Ties matched within .04', removed.