Certificate of Location of Government Corner

ID#: 743409 **Description:** SEC CEN 34 74 **Date Set:** 8/24/2006 **County:** Olmsted

Section: 34 **Township:** 107N **Range:** 14W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in grass area between off-ramp for TH 14 east and on-ramp for TH 52 south
This corner is located by GPS reference stations "TGI C & D"
Post w/sign 2' south

Corner History:

No date - Corner set in past surveys accurately, corner now large concrete monument with brass center set by Minn Hwy. Dept. in place of old used iron corner.

7-1975 County Surveyor found Conc. monu. with brass cap.

5-15-1989 McGhie & Betts found and used brass disc at center of section 34.

4-6-1999 Statement of evidence from MN/DOT survey crew corner location certificate. They located monument and mesured new reference ties.

The position for the corner is believed to have been originally established when a private surveyor placed an iron for the center quarter corner forty or more years ago. The Minnesota Highway Department Right-of-Way from around 1957 indicates a 1" square bolt for the corner. Although no documentation exists perpetuating the location of the found brass disk, it is accepted as marking the Center of Section 34, Township 107N, Range 14W because it accurately represents the true position for the corner.

3-5-2002 Mn/DOT survey crew found brass disk in concrete in good condition and took additional reference ties.

8-1-2002 County Surveyor found brass disc in concrete down 0.2' in good condition. Set 2 points and tied out corner for Hwy 52 construction.

8-24-2006 County Surveyor set 4' telspar w/CIC from computed coordinates at surface. Set sign & post 2' south.