Certificate of Location of Government Corner

ID#: 750105 **Description:** SEC COR 1 2 11 12 75 **Date Set:** 6/7/72 **County:** Olmsted

Section: 01 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1 1/2' south of centerline of E-W twp road and 3 1/2' east of N-S power line
Bottle cap in S side TP WSW 150.6'
Nail in E side TP S 30.75'
Bottle cap W side PP #40009 SSW 41.2'
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes Karrick 80.00 set post for corner to section 1-2-11-12 erected mound with trench, pitts, charred stake and Osage Orange seed at each angle.

6-1873 Thomas Hunter, Bk.A Pg.232; Shows a stone as the corner on his plat and also a stone at the 1/16 corner east.

1-1882 Thomas Hunter, Bk.A Pg.371; Found the stone and stake.

6-1930 John Kerr, Bk.3 Pg.41; Found the stone and the 1/16 stone east. He also set the 1/64 and the 1/16 North of the section corner.

6-7-1972 County Surveyor dug with tractor and found positive, undisputable corner stone found by J. Kerr and Hunter 1882 4" x 6" x16" shattered some by frost and age stone 7.15 East and 2.0' South of 1" square x 4' long rod set by McGhie as corner in line fences. Set 1-1/4" x 12" pipe with cap with reducer and 3/4" x 6" pipe coupled. Set small end down with CIM above and stone pieces near pipe below.

Note: This is a correction of a corner set by McGhie at an assumed location. The stone was 7.15' east and 2.0' south of the square rod set as assumed corner.

7-6-1999 County Surveyor found CIM in good condition.

3-17-2004 County Surveyor found CIM down 0.7' in good condition.