Certificate of Location of Government Corner

ID#: 750304 **Description:** 1/4 SEC COR 3 10 75 **Date Set:** 11/14/75 **County:** Olmsted

Section: 03 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

Post w/sign 155' north
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; West on true line between sections 3 & 10. 40.00 chs set quarter section post. RPs- 10" ironwood S41E 44 links, & 9" ash N20W 59 links.

1-1859 Samuel McDowell (P.65 No.91) shows 1/4 post used in breakdown of NE 1/4 of NW 1/4 sec 10.

1-1861 Samuel McDowell (Pg.65 N0.91), a surveyor found corner.

3-1864 P.C. Compton (P.79 No.119) used 1/4 corner to break down NW 1/4 sec 10. 1/16 West 19.95 chs. M&L to sec cor 1/16 South set M&L (no meas).

2-1871 Robert Perry (Pg.151 No.175), County Surveyor, found post planted as corner. Set 1/16 east midway and on line.

12-1893 W. Fraser (Pg. 540 No. 501) found post planted as corner. Set 1/16th east midway and on line.

11-14-1975 County Surveyor corner now comes in cultivated field. Set CIM (deep) over 3/4"x16" pipe as William Fraser's full measure from section corner 2-3-10-11 and on line from section corner 2-3-9-10. Dug at 1/16 east, but found nothing.

4-13-2004 County Surveyor found CIM in good condition down 1.0' in cultivated field.