Certificate of Location of Government Corner

ID#: 750305 **Description:** SEC COR 3 4 9 10 75 **Date Set:** 11/14/75 **County:** Olmsted

Section: 03 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls at NW corner of woods in line with old fences south and east
County Survey Disk in 12" twin Boxelder E 16.75'
County Survey Disk in 12" twin Oak SSE 54.42'
Post w/sign 2' south
This corner is located by GPS measurement

Corner History:

5-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; North between sections 9 & 10. 80.00 chs set post for corner to sections 3-4-9-10. RPs- 12" Hackberry S35W 33 links, 18" Hackberry N40W 78 links, 11" Hackberry N57E 51 links, & 18" Hackberry S40E 62 links.

3-1864 P.C. Compton (pg. 79 No. 119) used section corner for breakdown of NW 1/4 of section 10. Set 1/16th east midway and on line 19.95 chs.

1-1878 Thomas Hunter (Pg.326 No.320), County Surveyor found original corner lying on ground and stub of stake in ground. Tested by bearing trees standing and bearing tree stumps.

11-14-1975 County Surveyor dug 10'x10' with backhoe, but found nothing. Set CIM over 1/2"x18" iron rod as corner in line of fence east and at proportionate Gov't measure between 1/4 corner 4-9 and 1/4 corner 3-10.

4-13-2004 County Surveyor found CIM in good condition down 0.6' in corner of woods near field.