Certificate of Location of Government Corner

ID#: 750404 **Description:** 1/4 SEC COR 4 9 75 **Date Set:** 10/29/2003 **County:** Olmsted

Section: 04 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3 1/2' north of E-W fence and 1 1/2' west of fence south
Tree used as CP to fences S and W SE 4'
Post with sign 2' North
This corner is located by reference stations "Fay A & B"

Corner History:

5-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; West on true lin between sections 4 & 9. 40.00 chs set quarter section post. RPs- 10" sugar N45W 89 links, & 11" sugar S50E 48 links.

1-1878 Thomas Hunter (Pg.326 No.320), County Surveyor, reset a stake from bearing trees and stumps of bearing trees.

10-1910 Charles Larson (Pg.136B), County Surveyor, found wood stake.

1947 John Kerr (Bk.32 Pg.62), County Surveyor, used stone as 1/4 corner 4-9.

11-1960 John Kerr (Bk.80 Pg.57) found stone. Drove rods on east and north sides of stone.

10-28-1975 County Surveyor found 4" square topped limestone up 3" with a rod on the east side and a rod with a nut on north side as recorded by Kerr. Left as found.

10-7-2003 County Surveyor found 4" square topped limestone up 0.2' in good condition. Set post w/sign 2' North.

10-29-2003 County Surveyor removed stone and set 4' telspar pipe w/cast iron cap up 0.2' at stone position.