# Certificate of Location of Government Corner

**ID#:** 750409 **Description:** SEC CEN 4 75 **Date Set:** **County:** Olmsted

**Section:** 04 **Township:** 107N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

**Reference Ties:**

**Corner History:**

12-1856 Thos. Hunter (P.20 No.32) show center section with 3 B.T.'s (N 63° W 281 lks) (S 75° W 281 lks) (S 21-1/2° E 141 lks). 1/16 West 20 chs. M&L B.T.'s (N33° E 40 lks) (N 15° W 53 lks). 1/64 South 10.03-1/2 chs M&L B.T.'s (N 23-1/2° W 32 lks) (S 22° W 8 lks). 1/16 South 20.07 chs M&L stands in the river. B.T.'s (Elm N 11-3/4° E 92 lks). Section is broken in 1/4 of 1/4 of 1/4 with bearing trees to all corners used.
Note: 1/16 West stands in the river and a stake stands on the bank 50 links North of the 1/16 sec post.

2-1867 H.E. Horton (P.81 No.122) subdivision of NE 1/4 of NW 1/4 sec 4 (see survey for B.T.'s)

3-22-1892 T. Fraser (P.474) found center stake standing and marked SE B.T. standing taken by Perry Basewood S 21-1/2 E 14 L 9.24'. New B tree S 44° E 8-1/2 L 5.61' 10" red elm. Ran line West set stakes at 7-1/2 chs 495' and 12-1/2 chs 825'

1947 J. Kerr (B.32 P.62) Kalmar town board SW 1/4 4. Run line S 1/4 4 North 2624' used some kind of point as center elaborate survey in SW 1/4 4.

11-1975 County Surveyor checked fence post used as center section found post to be on E-W 1/4 line but ± 4' too far East (see sheet in file).

7-19-2004 V. Fangman computed center at intersecting quarter lines.