Certificate of Location of Government Corner

ID#: 750504 **Description:** 1/4 SEC COR 5 8 75 **Date Set:** 12/15/2004 **County:** Olmsted

Section: 05 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' south and 1' east of CP
10" blazed Oak in fence east ENE 26.50'
14" blazed Basswood N 12.00'
14" blazed Basswood SW 10.75'
Sign on CP 1 1/2' NW
This corner is located by GPS reference stations "Nepstad A & B"

Corner History:

1854 Gov't Notes: Karrick 40.00 set temp 1/4 section post. West on true line between section 5&8 9° 24'. 40.00 set 1/4 section post. Walnut 10 W 78 E 108. White Oak 13 S 10 W 3°

1870 R. Perry; Found gov't stake with bearing trees.

1901 W. Fraser; Caption above survey and set stone.

4-12-1971 County Surveyor walked to corner, found limestone up 4" above ground 2" x 12" x 20" set CIM in place of stone with 19" piece of T shaped steel fence post below with glass and alum pie plate around iron. Set 1-1/2" angle steel post 5' long up 3' just South of CIM, original stone just North of CIM with top of stone very near level of top of CIM. Corner came in NW corner small field on hilltop. Blazed 10" Oak Westerly of 3 in fence East, 5' N of E 26.5. Blazed 14" bass W in clump of 3 SW 10.75. Blazed 14" bass W terminal of fence wires E-N-S N 12.0.

12-15-2004 County Surveyor found CIM down 0.1' leaning NE. Removed and found T-bar. Removed T-bar and set 5.0' telspar pipe w/CIC at T-bar location. Replaced corner post. Put sign on SE side of new corner post.