# Certificate of Location of Government Corner

**ID#:** 750606 **Description:** W 1/4 SEC COR 6 75 **Date Set:** 8/7/1989 **County:** Olmsted

**Section:** 06 **Township:** 107N **Range:** 15W **Monument Description:** 5/8" Brass Plug

**Reference Ties:**

The corner falls in centerline of CSAH 5 and 1/2' south of centerline of twp road east
The monument is down 0.1'
County Highway Disc in south side of Power Pole #51193, West, 58.95'
County Highway Disc in leaning stub Power Pole, NE 56.17'
This corner is located by GPS measurement

**Corner History:**

1853 Gov't Notes: John Ball, Deputy Surveyor; North between sections 1 & 6. 40.00 chs set quarter section post. RPs; 10" burr oak S72°W 165 links, 5" burr oak N2°E 337 links.

8-24-1857 E.P. Bircher, Surveyor, per J.B. Fellows, Deputy (Old Road Book--Old Road No. 66) surveyed the road between Section 6, T107N,R15W, and Section 1, T107N, R16W.

12-1892 A.A. Crampton, Dodge County Surveyor,(Dodge County Records)found a limestone and the SW bearing tree.

1940 Dodge County Highway Dept. (Dodge county highway department Bk. 22) found a limestone at the corner. The corner was a P.I. (Delta=0D°33'Lt.) between the SW corner 6 and their assumed corner (hub) at the NW corner 6. Measured 2630.9 North to the hub at the NW corner 6.

11-15&16-1978 Olmsted County Surveyor dug for the corner, but couldn.t find the stone. The area had been subcut to clay.

3-25-1980 Olmsted County Surveyor set a 5/8"x16" rod as the corner from the SW bearing tree still standing (but dead). Measured South 2633.39 to the SW corner 6 and 2629.56 North to the Dodge County hub (not true corner) at the NW corner 6 (Delta=D°31'12"Lt.)

7-11-1985 Olmsted County Highway Department set 5/8" rod 105.13' ESE of the corner and on line to and nail and plastic disc in power pole #23119.

10-27-1988 Olmsted County Surveyor set a PK nail in the centerline crack of Co. RD. #5 by the tie and line from the RP iron East our Pt. is the measure of 105.13 Westerly of the RP iron this is 0.18' West and 0.02' North of the county highway department drill hole set in the summer of 1988.

8-7-1989 Olmsted County Highway Department set 5/8" brass plug in centerline C.R. #5. county highway department disc in PP W 58.95'. county highway department disc in stub pole NE 57.97'.

12-8-2004 Olmsted County Survey Crew found 5/8" brass plug in good condition.

10-23-2006 Olmsted County Survey Crew found 5/8" brass plug at surface in good condition.

7-14-2011 Olmsted County Survey Crew found 5/8" brass plug in good condition and updated ties.

5-22-2017 Olmsted County Survey Crew found 5/8" brass plug down 0.1' in good condition with grooves from concrete milling.