Certificate of Location of Government Corner

ID#: 751009 **Description:** SEC CEN 10 75 **Date Set:** 12/15/1976 **County:** Olmsted

Section: 10 **Township:** 107N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
3/4" pipe

Reference Ties:

The corner falls in a natural spring
Fiberglass post on south side of monument

Corner History:

1854 Gov't Notes: Karrick; 40.00 set 1/4 section post. RPs-10" black oak S 65 W32, 20" white oak N 50 E 50.

3-1864 P.C. Compton Pg. 79 No.119; shows 1/4 corner used for breakdown of NW 1/4 section 10. 1/16 east 20.18 chs. M & L to center section 10 found. 1/16 north set M & L (no measure).

8-1887 T. Hunter Pg.422 No.411; Found old stake set P. 79 No. 119 with witness tree stumps. Drove new stake well down and marked 1/4 S.

12-15-1976 T. Taylor set iron monument as corner for Prince Estates First Subdivision.

2-6-1981 T. Taylor found and used 3/4" pipe in survey in NW 1/4 section 10.

4-30-1999 V. Fangman found and used 3/4" pipe in survey of NW 1/4 and NE 1/4 of section 10.

2-21-2006 County Surveyor found 3/4" pipe in a natural sping in good condition.