Certificate of Location of Government Corner

ID#: 751105 **Description:** SEC COR 10 11 14 15 75 **Date Set:** 5/8/68 **County:** Olmsted

Section: 11 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' north of fence east and in line with fence north
Drag tooth in 36" Burr Oak NNW 7.35'
Post w/sign 2' north
This corner is located by GPS reference stations "Anway A & B"

Corner History:

1854 Gov't Notes: Karrick; 80.00 set post for corner to sections 10-11-14-15. Erected mound with trench, pits, charred stake, and planted osage orange seeds at each angle.

10-1858 T. Hunter Pg. 57 No. 83 used corern. 1/16th north M&L 19.95'

5-1870 R. Perry found bottom of old stake in mound with top lying on ground. Set boulder stone and new marked stake with old stake beside new one, renewed mound and pits. 16 east set stone and marked stake.

3-1873 T. Hunter Pg. 111 found corner in mound at 1/16th west set stake. M&L 19.94 1/2

1-1882 T. Hunter Pg. 371 No. 362 found stone and stake from Pg. 111 survey.

4-1892 Thomas Fraser Pg.482 No.459; Found stone set Pg.111, 16E found stone set by Perry ithstake on North side. 16N found stake set By Perry, reset by Hunter; set stone 5x8x25 in its place with bearing tree 12" black oak S 16° E 61 1/4 links.

5-8-1968 J. Kerr set CIM over iron sash weight with original stone on north side of CIM section corner. RPs- Steel fence post .5' west of CIM which fell 1'north of corner post, 7.35 NNW to drag tooth driven east side 36" burr oak.

6-8-1972 County Surveyor found boulder as 1/16 corner. Set 1/2"x4' rod over center stone.

12-7-1981 County Surveyor found CIM which stands 1' North of CP as recorded but the steel fence post is .5' South not .5' West as stated by J. Kerr 1968 notes.

10-31-2005 County Surveyor found CIM down 0.4' in good condition. Set post w/sign.