Certificate of Location of Government Corner

ID#: 751106 **Description:** 1/4 SEC COR 10 11 75 **Date Set:** 6/4/76 **County:** Olmsted

Section: 11 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 13' north of E-W fence and 3' east of fence north
County Survey Disk in 14" Elm NE 64.75'
County Survey Disk in E side CP S 13.28'
Spike & disc in 7" Elm WNW 11.16'
Steel post 1' west
Post w/sign 2' north
This corner is located by GPS reference stations "J.T. A & B"

Corner History:

6-1854 Gov't Notes: Michael Karrick, Deputy Surveyor; North between sections 10 & 11. 40.00 chs set quarter section post. RPs- 12" jack oak N50°W32 links, 11" jack oak N60°E40 links. 48.00 chs creek 3 links wide runs SE

6-1856 Thomas Hunter (Pg 11 No.18) found the 1/4 post

10-1858 T. Hunter (Pg.57 N0.83) found the 1/4 post. Set the 1/16 South midway and on line.

1-1882 T. Hunter (Pg.371 No.362), County Surveyor, found the stub of the old stake from the NW bearing tree and the stump of the NE bearing tree. Drove a new stake marked 1/4 corner.

4-1892 Thomas Fraser (Pg.482 No.460), County Surveyor, found the 1/16 south and set a stone 5"x8"x25" in its place.

12-1893 William Fraser (Pg.540 No.501), County Surveyor, found the stake.

6-4-1976 The County Surveyor dug for the corner, but didn't find anything. Set a CIM over a railroad spike as the corner by doubling the line and measure from section corner 10-11-14-15 over the 1/16 north (found).

9-9-2005 County Surveyor found CIM at surface in good condition. Set post w/sign.