# Certificate of Location of Government Corner

**ID#:** 751204 **Description:** 1/4 SEC COR 12 13 75 **Date Set:** 5/2/2002 **County:** Olmsted

**Section:** 12 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

**Reference Ties:**

The corner falls 26' south of fence west and 4' east of fence north
Post w/sign 2' North
This corner is located by GPS measurement

**Corner History:**

1854 Gov't Notes: Michael Karrick, Deputy Surveyor; West on true line between sections 12 & 13. 40.00 chs set quarter section post in mound with trench, pits, charred stake, and planted osage orange seed NE and SW.

6-1870 Robert Perry (Pg.122 No.157), County Surveyor, found stake in mound with pits plain. Set stone 5"x5 1/2"x19" with old stake by its side. Set stone at 1/16 east and north.

12-1971 County Surveyor found 1/16 stone north.

6-1972 County Surveyor ran north-south 1/4 line from 1/4 corner 1-12 over 1/16 found. Dug area of corner, but found nothing. Found 1/16 stone east.

4-6-1975 County Surveyor dug again after doubling the line and distance from the SE corner section 12 west over the 1/16 stone found, but found nothing. Set CIM over a 3/4"x10" iron rod at this location.

8-15-1983 County Surveyor found CIM too shallow. Replaced it with telspar pipe with CIC.

5-2-2002 County Surveyor found CIC in good condition down 2.5'. Set 21" CIM over CIC at surface. Set sign and post 2.0' North.