Certificate of Location of Government Corner

ID#: 751206 **Description:** 1/4 SEC COR 11 12 75 **Date Set:** 12/9/81 **County:** Olmsted

Section: 12 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in N-S fence and 11 1/2' south of fence line NE
County Survey Disk in W side PP #40017 (up 4') N 91.99'
Post w/sign 1' west
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes: Michael Karrick, Deputy Surveyor; North between sections 11 & 12 32.00 chs uncultivatable marsh NE; 40.00 chs set quarter corner in marsh, set witness quarter corner 3.50 North of this corner. Erected mound with trench, pits, charred stake, and planted osage orange seeds NE and SW.

6-1856 Thomas Hunter (Bk.A, Pg.11, No.18), County Surveyor, possibly used this corner to set the Center 12. He also set the 1/16 North of the Center 11.

6-1870 Robert Perry (Bk.A, Pg.122, No.157) may have used corner for subdivision of Section 12.

1-1882 Thomas Hunter (Bk.A, Pg.371, No.362) found hillock in mound with stakes close together a little west of old N-S wire fence and 4 lks North of midway and nearly on line.

12-2-1981 County Surveyor dug from 12' South of traverse nail South for 3 1/2', West 1', East 3 1/2", by 4' deep to clay (found nothing).

12-8-1981 County Surveyor dug again with backhoe South and East of the first hole. Found Nothing.

12-9-1981 County Surveyor set a CIC on a square pipe as the corner 4 links North of midway and at 3.96' West of a straight line between section corners as per T. Hunter's Survey No.362. T.Hunter's measures to the N-S quarter line of section 11 shows the quarter corner here 6 links=3.96' west of a straight line by measure. We used this since it places the corner under the N-S fence line. Set a survey marker sign and post .86' West of the monument. The corner is 11 1/2' South of the corner post to fences N-S-N-E.

4-22-2004 County Surveyor found monument up 0.4' in good condition.