Certificate of Location of Government Corner

ID#: 751209 **Description:** SEC CEN 12 75 **Date Set:** **County:** Olmsted

Section: 12 **Township:** 107N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

6-1870 R. Perry (P.122 No.157) set oak stake at inters lines. 1/16 North set stone 3 x 5-1/2 x 16 and stake oak M&L 19.99. 1/16 South set stone 4 x 5-1/2 x 18 and stake M&L 19.99. 1/16 East set boulder stone M&L 19.94 to 4-1/2 x 7 x 24 stone as East 1/4 section 12. Also set stone 3 x 5-1/2 x 15 and stake for line East M&L 9.99 South of above 1/16 corner. 1/16 center NE 1/4 12 set stone 2-1/2 x 8 x 20. 1/16 center SE 1/4 12 set stone 5 x 5 x 15 line East meas South of center SE 1/4 12 to 1/16 on section line 19.98-1/4.

11-11-1971 County Surveyor walked to area, no E-W fences at all. Large post with brace could be site of Perry's corner. Would have to be proven. N-S fence should be close.

8-13-2004 V. Fangman computed center at intersecting quarter lines.

3-24-2006 McGhie & Betts use computer center at intersecting quarter lines.