Certificate of Location of Government Corner

ID#: 751306 **Description:** 1/4 SEC COR 13 14 75 **Date Set:** 5/10/68 **County:** Olmsted

Section: 13 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' west of N-S fence and 78' south of fence east
County Survey Disk in S side split Boxelder SW 72.60'
County Survey Disk in W side of wood fence post S 15.51'
Steel fence post 1/2' SW
This corner is located by GPS measurement

Corner History:

1854 Gov't Notes Karrick 40.00 set 1/4 section post. Bur Oak 8 S 75 W 106. Jack Oak 12 N 63 E 53.

3-1873 T. Hunter (P.217 No.221) caption of 10-29-1879 set W 1/4 a stone by using 1/4 13-14 (E 1/4 14) over center both in place. In 1873 survey W 1/4 14 in frozen road and not found.

8-1967 J. Kerr run line from NE 14 to SE 14 both CIM's set as near as possible by records etc. Total mile 5282 + set 3/4 x 18" rod at 2640 on line.

5-10-1968 J. Kerr set CIM as 1/4 corner over 1" x 12" pipe. Set 3/8" rod 1" East of fence which lies 1' North of 11th steel post.

3-20-1985 V. Fangman found corner 0.5 West of N-S fence, 78' South of fence to East, and 0.5' NE of a steel fence post. RP: 8d nail in 30" Oak NE 138.92'. 8d nail in 24" Willow NW 65.67'.

4-22-2004 County Surveyor found CIM in good condition down 0.8'