Certificate of Location of Government Corner

ID#: 751805 **Description:** W SEC COR 18 19 75 **Date Set:** 7/7/1972 **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

Center of 30" Basswood NE 6.3'
Center of 20" Red Oak SW 9.5'
Steel fence post 1'
Post with sign 2' south
This corner is located by GPS reference stations "Wharton B & C"

Corner History:

1854 Gov't Notes Set corner post to 13-18-19-24. RPs-16" burr oak S 27° W 61 links, 18" black oak N 35° W 47 links,16": black oak N 45° E 59 links, 18" black oak S 40° E 60 links.

6-1895 W. Fraser Pg.578 No.528; Found stake set by Dodge County Surveyor, F. Pendergast. Tested stumps of all 4 bearing trees, proved correct. Set stone 3x8x30 as corner. 1/16 east set stone 5x5x18 on line at 18.71 then 19.83, to N 1/4 19. A stone 4x10x18" set this survey.

12-1900 W. Fraser Pg.702 No.617; Found stone set Pg. 578. 1/16 east found corner set Pg. 578. East set stake at 2.77 1/4 then stake 4.06 1/4 then stone at 5.08' then 679 to 1/16 corner described above, all for lines north.

8-18-1964 J. Kerr set CIM over 1"x24" steel. RPs-Center 30" basswood NE 6.3', Center 20" red oak SW 9.5', steel fence post N 0.8'.

12-15-1970 Olmsted County Surveyor found CIM broken in half.

7-7-1972 Olmsted County Surveyor found CIM, replaced after found broken in 1970.

12-8-2004 Olmsted County Surveyor found CIM down 0.8' in good condition.

12-15-2004 Olmsted County Surveyor set post with sign 2.0'.

1-26-2010 Olmsted County Surveyor found CIM down 0.8' in good condition.