Certificate of Location of Government Corner

ID#: 751809 **Description:** Center **Date Set:** **County:** Olmsted

Section: 18 **Township:** 107N **Range:** 15W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Square punch hole in East end 36" CMP N 48.60'
Top center of gas valve at the NW corner of house SW 102.08'
Spike with ribbon in PP #22046 W 115.57'
Nely corner of concrete slab in front of step at the NE corner of house NW 153.11'

Corner History:

1-30-1893 William Fraser, County Surveyor, (Bk.A,Pg. 503, No.473) found stake set by Thomas Fraser in 1890 unrecorded survey (Old Fieldbook 7, Pg. 2-3). Also found stake at the 1/16 East placed midway (19.80 & 3/4 chs.) and on line in the 1890 survey.

10-11-1900 William Fraser, County Surveyor, (Bk.A, Pg.702, No.617 and Old Fieldbook 9, Pg.89) found stake by corner of fence. Used the corner to set the 1/16 West and several other property corners in the W 1/2 SW 1/4 section 18.

4-8-1971 County Surveyor found a pipe believed set by Highum, the Dodge County Surveyor. Ran the 1/4 lines of section 18 and found that the pipe was not on either 1/4 line.

5-16-1977 County Surveyor set a temporary point (120d spike) at intersecting 1/4 lines. Removed pipe found 7.59 North and 8.16 East.

6-24-1977 McGhie & Betts found and used 120d spike.

4-3-1978 Yaggy Associates used computed center.

6-2-1978 County Surveyor set a 5/8"x18" rod from references taken 5-16-1977 and in newly graded crushed rock road.

3-8-2005 County Surveyor visited area of corner and found nothing. Ties still in place.