Certificate of Location of Government Corner

ID#: 752105 **Description:** SEC COR 20 21 28 29 75 **Date Set:** 8/26/65 **County:** Olmsted

Section: 21 **Township:** 107N **Range:** 15W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under N-S fence and 125' S of centerline of E-W waterway
Post w/sign 1' west
This corner is located by GPS reference stations "Dusty A & B"

Corner History:

1854 Gov't Notes: Karrick; 80.00 set post for corner to section 20-21-28-29 and erected mound with trench,pits,charred stake, and osage orange seeds at each angle.

5-1872 T. Hunter Pg.197 No.207; Found stone set as corner with original stake beside it. Measured north 39.90 to temp. Stake set M & L,, measured east 39.93 to 3x8x15 stone set M & L.

6-1876 T. Hunter Pg.296 No.291; Found stone pg.197 in mound by original stake. North set stone 5x6x17 at 9.98 7/8 to stone set later in 1886 as 1/16 corner then 19.97 3/4 to corner set M & L pg.253.

1936 county highway department Book #84 Pg.72; Found 8"x8"x4" limestone 65' south of fence corner in line of fence running north.

8-26-1965 J. Kerr set CIM over 1/2"x2' rod in stones. 1/16 stone north 657.3 should be 659.18 (real good). Line of this stone must be east to be on true N-S line. RP to sec. Cor.-Random fence between pasture and fields to south, running east S70.0(gone1979).Center line of natural waterway ditch running generally east and west N 125.0', Corner directlyy under fence N-S, no E-W fence.

9-6-1979 County Surveyor set survey marker sign 1' west of CIM, fence East and south now gone. Measured 120' north to center creek.

5-29-2002 County Surveyor found CIM down 0.3' in good condition.